

### Description

Reduces tool wear and improves machined finish. A ready to use cutting and tapping fluid specially formulated to improve tool performance and extend tool life. It contains additives to prevent pitting, galling and metal seizure and is suitable for use on aluminium and steel.

### Benefits & Features

- For cutting, tapping, reaming and turning
- Extreme pressure additives
- High pressure, frothy discharge to aid penetration
- Prolongs tool life and improves machined finish
- Reduces heat build up
- Incorporates corrosion inhibitors

### Directions for Use

Shake can well before use. Spray tool area to be treated. Repeat if necessary. **Do not spray onto very hot surfaces or near naked flames.**

### Technical Data

Appearance:	Brown, frothy liquid-viscosity 300cPs
Odour:	Sweet solvent odour
Contents:	Blend of naphthenic lubricants, petroleum wax, bitumens, polyisobutylenes, minor quantities of xylene and white spirit, viscosity improvers, extreme pressure additives, corrosion inhibitors and hydrocarbon propellants. Non-chlorinated
Storage:	Below 50°C
Flash Point:	<0°C
Relative Density:	0.840
Solubility:	Insoluble in water
Temperature Range:	Designed for use at ambient temperatures

### Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

