

Description

Provides a tenacious lubricant film to exposed gears and wire ropes. A bituminous reinforced heavy duty lubricant formulated to protect and lubricate exposed gears, wire ropes and other moving parts. Exceptional penetrating and water resistance properties make it ideal for situations where exposure to weather is experienced and its tenacity resists throwing off during use.

Benefits & Features

- Highly resistant to throw off
- Water resistant for use in adverse weather conditions
- Good penetrating qualities
- Excellent lubricating power
- High pressure foaming discharge imparts excellent penetrative power
- Protects against corrosion, wear and salt
- Resistant to embrittlement over long usage

Directions for Use

Shake can well before use. Spray onto stationary parts from 20 to 30cm. The directional nozzle assists in accurate positioning of the lubricant.

Technical Data

Appearance:	Dark brown frothy foam drying to a sticky viscous state
Odour:	Mineral oil odour
Contents:	Blend of petroleum distillates, mineral oil, xylene, bitumen, anti-fling and extreme pressure additives, and hydrocarbon propellants
Storage:	Below 50°C
Flash Point:	<0°C
Relative Gravity:	0.900
Solubility:	Insoluble in water
Temperature Range:	Designed for use at ambient temperatures



Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.