

Description

Premium lubrication that's effective yet safe. Provides clean, low odour, non-staining lubrication for most applications, especially plastic parts and seals.

Benefits & Features

- Excellent lubricating properties
- Non-staining, low odour
- Effective on plastic, metal, wood, vinyl, rubber and other surfaces
- Used for mould release in the plastics industry
- An effective surface polish
- Use on seals, slides, bearings, textile equipment etc.
- High temperature stability
- Water repellent

Directions for Use

Shake can well before use. Spray onto surface from 20-30cm. Remove excess with a clean cloth. **Should not be used on surfaces where subsequent re-finishing is to take place eg. painting, printing.**

Technical Data

Appearance:	Clear water white liquid
Odour:	Slightly sweet when dried
Contents:	Blend of 9% silicone, quick drying solvent and hydrocarbon propellants
Storage:	Below 50°C
Flash Point:	<0°C
Dielectric Properties:	At 25°C on a 30 micron film at 50% RH Dielectric Constant: 100Hz to 100MHz = 2.75 Dielectric Breakdown: 30Kv/mm
Relative Density:	0.795
Solubility:	Insoluble in water
Temperature Range:	-50° to 200°C (Continuous)/250°C (Intermittent)



Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.