

Description

Effectively prevents the adhesion of weld spatter. A water based solvent-free formulation for use on all types of welding equipment to prevent the adhesion of welding spatter. It can be applied to workpieces, nozzles, shrouds, jigs and tools. Its water based properties offer an environmentally friendly alternative to solvent based varieties.

Benefits & Features

- Prevents spatter adhesion
- Non-silicone – can be used with products that require finishing
- Excellent non-stick finish
- Non-flammable
- Water rinseable
- Dichloromethane free

Directions for Use

Shake can thoroughly before use and spray component sparingly from of a distance of 20 to 30cm, ensuring even coverage.

Technical Data

Appearance:	Pale yellow liquid
Odour:	Slight vegetable oil
Contents:	Emulsion of refined vegetable oils, alcohol ethoxylate emulsifier, anionic surfactants, and trace quantities of diethanolamine anti corrosion additive in de- ionised water, with nitrogen propellant
Storage:	Below 50°C
Flash Point:	Not classed as flammable
Relative Density:	1.00
Solubility:	Soluble in water
Temperature Range:	Not applicable

Please Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

