

### Description

Powerful protection from heat and the elements

A high temperature multi purpose blend of heat stable lubricant and anti seize compound used in a wide range of automotive, industrial, marine and construction applications, helping to eliminate seizure, pitting and rusting of components exposed to heat. Use on threaded components, flanges, chains and locks to facilitate in future dismantling.



### Outstanding Features

- Prevention of seizure
- Assists in easy dismantling of threaded parts
- Effective lubrication at ambient temperatures
- High temperature resistance to melting
- Use also on flanges, chains and locks
- Facilitates easy re use of dismantled components

### Directions for Use

Shake can thoroughly, until the agitator rattles freely and spray sparingly onto components from a distance of 20 to 25cm, ensuring an even coat, prior to assembly. Both contact surfaces should be completely coated for optimum results.

### Technical Data

Appearance	Silver viscous liquid
Odour	Sweet solvent
Contents	Blend of micronized aluminium, molybdenum disulphide, inert clay, and naphtha in a synthetic ester, with propane/butane propellant
Storage	Below 50°C
Flash Point	<0°C
Temperature range	Continuous 275°C. Anti seize range -30° to 800°C
Relative Density	0.915
Solubility	Insoluble in water
Boiling Point	-40°C
Pack Sizes	12 x 400ml cans

The content of this data sheet is given in good faith but without warranty.