

### Description

Highly effective, instant detection of gas leaks

An inoffensive, non-corrosive foam used in the inspection of pipework to prevent leaks passing unnoticed with potentially dangerous effects. It will detect any leaks instantly and is harmless to most materials as well as being safe to use with most other gases.



### Outstanding Features

- Non-flammable water based
- Completely inert
- Will detect the smallest leaks
- Will not form combustible mixture with other gases
- Can be used with oxy-acetylene and LPG gases
- Non-corrosive
- Nitrogen propellant
- Easily removed – completely water soluble
- Conforms to BS EN ISO 14921 EU Regulations for use in Department of Transport testing stations

### Directions for Use

Shake can well before use. Spray liberally onto suspected area of leak. A stream of bubbles will indicate the exact source of the leak.

### Technical Data

Appearance	Clear/white slightly foaming liquid
Odour	Virtually odourless
Contents	Blend of ethanediol, ethoxylated alcohol and corrosion prevention additive in demineralised water with nitrogen propellant
Storage	Below 50°C
Flash Point	Non-flammable
Temperature range	Designed for use at ambient temperatures
Relative Density	1.02
pH	7-7.5
Solubility	Soluble in water
Pack Sizes	12 x 400ml cans

The content of this data sheet is given in good faith but without warranty.